



Previous Name: Shell Tellus TD

# Shell Tellus S2 VA 46

- Water Tolerant
- Versatile Applications

*Industrial Detergent Hydraulic Fluid for wide temperature range*

Shell Tellus S2 VA is a high performance detergent-based hydraulic fluid for use where emulsifiable fluids are preferred. Using proven zinc-based anti-wear technology it provides proven performance in applications such as construction or mobile applications where contamination by water, cleanliness or control of solid contaminants is important in conjunction with a wide range of operating temperatures.

## DESIGNED TO MEET CHALLENGES

### Performance, Features & Benefits

#### • Protection in severe environments

The established detergent and zinc based anti-wear technology in Shell Tellus S2 VA fluids provides extra protection in challenging environments by:

- Preventing water accumulation
- Dispersing solid contaminants
- Preventing corrosion in presence of water
- Providing low-friction anti-wear performance

In addition, the high viscosity index helps ensure protection and performance from low-temperature start-up conditions to high temperature and severe duty operations.

#### • Fluid life – Maintenance saving

Shell Tellus VA fluids have good resistance to thermal and chemical breakdown to ensure consistent performance and protection throughout the fluid drain interval.

#### • Maintaining system efficiency

Superior cleanliness in severe environments helps keep the hydraulic system functioning efficiently. This is supported by excellent air release and anti-foam characteristics.

In addition, Shell Tellus S2 VA provides excellent filterability allowing the use of fine filters for extra protection and long equipment life.

Smooth operation of the hydraulic system is supported by the low-friction additive system that helps reduce stick-slip behaviour under high loads or poorly lubricated contacts.

Shell Tellus S2 VA are manufactured with a Quality System assuring the fluid at the Shell plant filling lines meets the requirements of max ISO 4406 21/19/16 class.

As recognized by DIN 51524 specification, the oil is exposed to various influences with transport and storage that could effect the cleanliness level.

### Main Applications



#### • Mobile Equipment

Earth moving equipment and similar units subjected to the most severe outdoor operating conditions.

#### • HLPD Oil recommendations:

All hydraulic systems for which an HLPD oil is specified.

#### • Engine Oil Hydraulic Applications

Hydraulic systems which specify the use of engine oils meeting SAE 10W, 20W-20 or 30 viscosity classifications

#### • Other applications

Certain industrial gearboxes.

### Specifications, Approvals & Recommendations

- DIN 51502 (HVLPD fluids)
- ISO 6743/4 (L-HV fluids)
- ISO 11158 (HV fluids)
- ASTM 6158-05 (HV fluids)

For a full listing of equipment approvals and recommendations, please consult your local Shell Technical Helpdesk, or the OEM Approvals website.

## Compatibility & Miscibility

### • Compatibility

Shell Tellus S2 VA fluids are suitable for use with most hydraulic pumps. However, please consult your Shell Representative before using in pumps containing silver plated components.

### • Fluid Compatibility

Shell Tellus S2 VA fluids are compatible with most other mineral oil based hydraulic fluids. However, mineral oil hydraulic fluids should not be mixed with other fluid types (e.g. environmentally acceptable or fire resistant fluids).

### • Seal & Paint Compatibility

Shell Tellus S2 VA fluids are compatible with seal materials and paints normally specified for use with mineral oils.

## Typical physical characteristics

Properties			Method	Tellus S2 VA 46
ISO Viscosity Grade			ISO 3448	46
ISO Oil Type				L-HV
Kinematic Viscosity	@40°C	cSt	ASTM D 445	46
Kinematic Viscosity	@100°C	cSt	ASTM D 445	9.3
Viscosity Index			ISO 2909	185
Density	@15°C	kg/l	ISO 12185	874
Flash Point (COC)		°C	ISO 2592	190
Pour Point		°C	ISO 3016	-54

These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in these characteristics may occur.

## Health, Safety & Environment

- **Guidance on Health and Safety is Available on the appropriate Material Safety Data Sheet, which can be obtained from <http://www.epc.shell.com/>**

### • Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.

## Additional Information

### • Advice

Advice on applications not covered here may be obtained from your shell representative.

## Viscosity - Temperature Diagram for Shell Tellus S2 VA 46

